

*Tar Solve is a tough, fast acting solvent that removes tar, bunker C and asphalt from trucks, autos, equipment, tools, etc. For spot treatment only.*



### Where To Use

Detail Shops      Car Washes

### Dilution

As is.

### Directions

Spot check surface to be cleaned. Tar Solve can be used straight or cut up to 1/10 with kerosene. Either rub on with rags or low pressure spray on surface. Do Not apply to hot car or similar hot surfaces. Pressure rinse thoroughly with cool water when done. Do Not apply to plastic surfaces. Use cautiously on painted surfaces, will craze polystyrene. Do Not allow to dry on glass or paint surfaces.

### Technical Specifications

COLOR: .....	Transparent Green	VISCOSITY: .....	Water Thin
FORM: .....	Liquid	STORAGE(Unopened):..	1 Year @R.T.
SCENT: .....	Solvent	BIODEGRADABLE: ...	Yes
pH: .....	N/A	WEIGHT/GAL: .....	7.5 lbs.
FLASH POINT: .....	113° F	SHIPPING CLASS: .....	Combustible
FOAM: .....	None	PACKAGING: .....	5 gal, 55 gal
TYPE: .....	Solvent Based Tar Remover		



# MATERIAL SAFETY DATA SHEET

Simoniz USA Inc.

201 Boston Turnpike  
Bolton, CT 06043

(860) 646-0172

REVISION DATE:.....02/13/02  
DATE PRINTED:.....02/08/07

PRODUCT NUMBER:.....T3780XXX  
CONTROL NUMBER:.....T3780XXX

## SECTION I - IDENTIFICATION

PRODUCT NAME: **Tar Solv**

PRODUCT TYPE:.....Solvent Based Cleaning Compound

## SECTION II - INGREDIENTS

INGREDIENT	CAS NUMBER	PEL	PERCENT
Light Aromatic Solvent Naptha	64742-95-6	400 ppm PEL	<b>Not Listed.</b>
Isoparaffinic Solvent	64742-47-8	300 ppm	
Detergent Range Alcohol Ethoxylate	68439-46-3	No limits established	

## SECTION III - PHYSICAL DATA

APPEARANCE: Green transparent liquid, solvent odor.

BOILING POINT: 313 degrees F.

VAPOR DENSITY: Greater than 1.

PH: NA

VAPOR PRESSURE: <5 mm Hg

SPECIFIC GRAVITY: 0.87

SOLUBILITY IN WATER: Insoluble.

## SECTION IV - FIRE AND EXPLOSION DATA

FLASHPOINT:.....114 degrees F.

EXTINGUISHING MEDIA:.....Water fog or fine spray. Carbon dioxide, Dry chemical, or Alcohol resistant foam.

SPECIAL FIRE FIGHTING PROCEDURES:.....Firefighters working in areas where this product is present should be equipped with an approved, fully enclosed SCBA .

UNUSUAL FIRE AND EXPLOSION HAZARDS:.....None known.

## SECTION V - REACTIVITY DATA

STABILITY:.....Stable under normal conditions.

HAZARDOUS POLYMERIZATION:.....This product not known to polymerize.

INCOMPATIBILITY:.....Do not mix with other chemicals.

HAZARDOUS BYPRODUCTS:.....Carbon monoxide, carbon dioxide.

## SECTION VI - HEALTH DATA

ROUTE(S) OF ENTRY:.....Inhalation, skin absorption, or ingestion.

LISTED CARCINOGEN:.....Not listed by IARC, NTP or OSHA.

MEDICAL CONDITION AGGRAVATED:.....May aggravate pre-existing dermatitis.

INHALATION:.....Not likely to be inhaled in hazardous amounts. Avoid exposure to mists or vapors. Maintain adequate ventilation in the work area.

INGESTION:.....Swallowing even small amounts may be harmful. Effects may be nausea, headache, vomiting and central nervous system depression.

EYES:.....May cause severe eye irritation.

SKIN (DERMAL):.....This product may cause irritation if not removed from the skin. Prolonged exposure may cause central nervous system depression.

## SECTION VII FIRST AID

BREATHING (INHALATION):.....If victim shows signs of discomfort or irritation, remove to fresh air. If symptoms persist, get immediate medical attention.

SWALLOWING (INGESTION):.....DO NOT INDUCE VOMITING! Drink a large quantity of water or milk. Do not attempt to give liquids to an unconscious person. Get immediate medical attention!

EYES:.....Flush eyes with a large quantity of fresh water for at least 15 minutes. If irritation persists, consult a physician.

SKIN (DERMAL):.....Flush from skin and clothing with large amounts of fresh water. If irritation persists, consult physician. Wash contaminated clothing before wearing.

## SECTION VIII EMPLOYEE PROTECTION

RESPIRATORY PROTECTION:.....Not usually needed in well ventilated areas. If needed, use an OSHA approved respirator.

PROTECTIVE CLOTHING:.....Nitrile or PVC gloves, and chemical splash goggles.

ADDITIONAL MEASURES:.....Do not place this product in an unmarked container! Keep away from children! Spilled material is slippery.

## SECTION IX - SPILL AND DISPOSAL DATA

SPILL:.....Dike to prevent spillage into streams or sewer systems. Consult local, state and federal authorities.

WASTE DISPOSAL:.....As recommended by local, state and federal authorities.

HANDLING & STORAGE PRECAUTIONS.....Store in a cool, well ventilated area. Avoid overheating or freezing.

## SECTION X - OTHER REGULATORY INFORMATION

PROPER SHIPPING NAME: Not D.O.T. regulated in these container sizes.

NFPA HEALTH: 2

CONSTITUENT:

NFPA FLAMMABILITY: 2

HAZARD CLASS AND LABEL:

NFPA REACTIVITY: 0

ID NUMBER:

NFPA OTHER: None

PACKING GROUP:

## SECTION XI - PRECAUTIONARY STATEMENTS

WARNING:.....The information contained in this MSDS is based on the data available to us from sources we believe to be reliable. No warranty or guaranty expressed or implied is made regarding the accuracy of this data or the results obtained from the reliance on this data. The manufacturer assumes no responsibility for injury from the use of this product. Be safe- read this product safety information and pass it on to all persons who may be exposed to this product. Federal law requires it.