




Foamy Tire & Motor

The high foaming action of Foamy Tire & Motor work well in self-serve, whitewall and motor degreasing applications. Simply spray on and rinse off to quickly remove grease, dirt and road film.



Features and Benefits

- Works with wands, CTAs and hand sprayers
- Phosphate free
- Biodegradable

Technical Information

Form — Liquid
Color — Green
Odor — Slight
Foam — High

Product Usage Ratio

CTA application
10:1 - 5:1 wet tire
25:1 - 10:1 dry tire

NOTE: See reverse side for MSDS information and General Cautions for Use

Product Information

Product Code
EXT 195



MATERIAL SAFETY DATA SHEET

(COMPLIES WITH 29CFR 1910.1200)

SECTION I - CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Identity (As Used on Label and List): Extreme Foamy Tire & Motor
Product Class: Water-based degreaser
Emergency Telephone Number: 800-535-5053 (INFOTRAC)
Telephone Number for Information: 763-509-7937
Manufacturer's Name and Address:
Ver-tech Labs
6801 Bleck Drive
Rockford, MN 55373

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components (Specific Chemical Identity):

Chemical	Common Name(s)	%
A	2-butoxy ethanol CAS #111-76-2	1 - 5
B	Sodium xylene sulfonate CAS #1300-72-7	1 - 5
C	Sodium hydroxide CAS #1310-73-2	10 -20
D	Tetrasodium EDTA tetrahydrate CAS # 64-02-8	1 - 5
E	Water CAS #7732-18-5	60 - 100

SECTION III - HAZARDS IDENTIFICATION

Emergency Overview

Appearance and Odor: Red liquid, solvent odor.
Primary Hazards: Corrosive

Potential Health Hazards

Route(s) of Entry: Skin Absorption: X Ingestion: X Inhalation: X
Eye: Causes chemical burns.
Skin: May cause chemical burns.
Ingestion: Harmful if swallowed.
Inhalation: Overexposure to 2-Butoxy ethanol (butyl) vapors may cause central nervous system effects including drowsiness, headaches, nausea and dizziness.
Signs and Symptoms of Exposure: Irritation on direct contact.
Carcinogenicity: NTP? No IARC Monographs? No
OSHA Regulated? No

Target Organ (s): 2-butoxy ethanol ("butyl"): Liver, kidneys, lymphoid system, skin, blood, eyes and respiratory system.

Medical Conditions Generally Aggravated by Exposure: N. Av.
Health Hazards, Chronic: Overexposure to 2-Butoxy ethanol (butyl) may cause damage to one or more of the target organs listed above.

SECTION IV - FIRST AID MEASURES

Emergency and First Aid Procedures:

If Swallowed: Do not induce vomiting. Drink water in large amounts and call a physician immediately. Never give anything by mouth to an unconscious person. **Eye Contact:** Flush eyes with running water for at least 15 minutes. If irritation persists, obtain medical attention. **Skin Contact:** Flush thoroughly with cool water. Remove and wash contaminated clothing before reuse.
Sources Used: Raw material data, general toxicology from the trade for similar products.

SECTION V - FIRE FIGHTING MEASURES

Flammability: No **Autoignition Temperature:** N. Av.
Flash Point (method used): None
Flammable Limits: N. Av. LEL UEL
Extinguishing Media: N. Av.
Water? Foam? Water Fog?
Alcohol Foam? CO₂? Dry Chemical?
Vaporizing Liquid? Other?

Special Fire Fighting Procedures: N. Av.
Unusual Fire and Explosion Hazards: N. Av.
TDG Flammability Classification: Non-flammable
Sensitivity to Mechanical Impact: None
Sensitivity to Static Discharge: None

SECTION VI - ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case Material is Released or Spilled:
Dike and contain spill with inert material (sand, earth, etc). Collect spill with mop, absorbent material (example: floor-dri) or vacuum. Thoroughly rinse affected area with water.

SECTION VII - HANDLING AND STORAGE

Precautions to be Taken in Handling and Storing:

Normal care in handling and storage.
Other Precautions: Keep out of reach of children. Keep from freezing.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection (Specify Types): Not required
Ventilation: Local Exhaust: Not required **Special:** Not required
Mechanical (General): Ventilate to keep vapor levels below PEL
and TLV, listed in Section XI. **Other:** Not required
Protective Gloves: Natural rubber or synthetic.
Eye Protection: Approved safety goggles or glasses. **Footwear:** Chemical resistant

Other Protective Clothing or Equipment: Not required

Work/Hygienic Practices: Do not contaminate food or beverages with cleaning chemicals.

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Approximately 212°F **pH:** 13
Specific Gravity (H₂O) = 1: 1.11 **% Volatile:** > 75
Vapor Density (Air = 1): > 1 **Odor Threshold:** N. Av.
Evaporation Rate (Butyl Acetate = 1): N. Av. **Oil/Water Distribution Coefficient:** N. Av.
Solubility in Water: Complete
Vapor Pressure (MM HG): N. Av.
Melting Point: N. Av.

SECTION X - STABILITY AND REACTIVITY

Stability: Unstable: Stable: X
Conditions to Avoid: N. Av.
Incompatibility (materials to avoid): N. Av.
Hazardous Decomposition or By-products: N. Av.
Hazardous Polymerization: May occur: Will not occur: X
Conditions to Avoid: N. Av.

SECTION XI - TOXICOLOGICAL INFORMATION

Chemical	OSHA PEL	ACGIH TLV	Recom.	LD50	LC50
A	25 ppm (skin)	25 ppm (skin)	25 ppm	1.48 g/kg (rat, oral)	N. Av.
B	N. Av.	N. Av.	N. Av.	4,000 mg/kg (rat, oral)	N. Av.
C	2 mg/M ³	2 mg/M ³	N. Av.	140-340 mg/kg (rat, oral)	N. Av.
D	N. Av.	N. Av.	N. Av.	>2,000 mg/kg (rat, oral)	N. Av.
E	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.

Teratogen, Mutagen, Reproductive Toxin Status: No known relevance to humans.
Toxicologically Synergistic Products: N. Av.

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicological Information: N. Av.
Chemical Fate Information: N. Av.

SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Dispose of spilled material in accordance with local, state and federal regulations. Waste from normal cleaning procedures may be sewer, depending on the materials and/or contaminants being cleaned as well as state, federal and local sewer commission regulations.

RCRA Hazard Class: D002, characteristic corrosive

SECTION XIV - TRANSPORT INFORMATION

Shipping Classification: Corrosive liquid, basic inorganic, N.O.S. (Containing sodium hydroxide), Class 8
UN Number: 3266
Packing Group: II

SECTION XV - PREPARATION DATA

Prepared By: Health and Safety Department
Telephone Number: 763-509-7937
Date: 3-21-2005

SECTION XVI - REGULATORY INFORMATION

US Federal Regulations

TSCA Status: All ingredients listed.
CERCLA Reportable Quality: N. Av.

SARA Title III

Section 302 Extremely Hazardous Chemicals: None
Section 311/312 Hazard Category: Immediate health, chronic health.
Section 313 Toxic Chemicals: 2-butoxy ethanol (glycol ether)

SECTION XVII - OTHER INFORMATION

None

N. Av. - Not Applicable; N. Av. - Not Available

NFPA SYSTEM

2 A. Health Hazard 0 A. Fire Hazard 0 A. Reactivity Hazard

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. MINUTEMAN INTERNATIONAL, INC. ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.